

IEC 61850 User Feedback Task Force - Support #419

Also many other features of GOOSE messaging are left to the manufacturer to choose.

02/03/2021 02:07 PM - Herbert Falk

Status:	In Progress	Start date:	
Priority:	Normal	Due date:	
Assignee:		% Done:	0%
Category:	Standard options reduction required	Estimated time:	0.00 hour
Target version:		Spent time:	0.00 hour
ID:	10.2	Discuss in Upcoming Meeting:	No
Source:	ENTSO-E	To discuss in WG10:	No
TF Unique ID:	10.2 # ENTSO-E	Short Proposal:	Some of the GOOSE options maynot be required
WG10 Proposal:	some Options may be eliminated; will be analysed by WG10. Example PIXIT_GS4: the behaviour should probably be defined in the standard.To review all PIXIT with regard to (a) eliminate them by making the standard stronger or (b) transfer them to the PICS/service section of SCL file to make them machine processable.(20180613)WG 10 (completion date Ed 3), standard 7-2, for example PIXIT Gs4 should be defined in standard? To review complete PIXIT with regards:a) eliminate them by making the standard stronger or b) transfer them to the PICS/service section of SCL to make them machine processablec) If a lower value StNum is received and it is not the case of rollover and there is no communication loss then the older/lesser StNum shall be ignored. – to update 7-2. (Thierry D., Herb F.). To check 8-1 in case that there is a need for a change (Herb F.).	Standard(s):	IEC 61850-7-2
Estimated Completion:	ED3 (Tasl leader to inform editors 7-2)		
Description			
Also many other features of GOOSE messaging are left to the manufacturer to choose.			

History

#1 - 02/03/2021 02:49 PM - Herbert Falk

- Status changed from New to In Progress

#2 - 06/14/2022 09:33 AM - Vladan Cvejic

- WG10 Proposal changed from some Options may be eliminated; will be analysed by WG10. Example PIXIT_GS4: the behaviour should probably be defined in the standard.

To review all PIXIT with regard to (a) eliminate them by making the standard stronger or (b) transfer them to the PICS/service section of SCL file to make them machine processable.

(20180613)

WG 10 (completion date Ed 3), standard 7-2, for example PIXIT Gs4 should be defined in standard? To review complete PIXIT with regards:

a) eliminate them by making the standard stronger or

b) transfer them to the PICS/service section of SCL to make them machine processable

c) If a lower value StNum is received and it is not the case of rollover and there is no communication loss then the older/lesser StNum shall be ignored.

– to update 7-2. (Thierry D., Herb F.). To check 8-1 in case that there is a need for a change (Herb F.). to some Options may be eliminated; will be analysed by WG10. Example PIXIT_GS4: the behaviour should probably be defined in the standard. To review all PIXIT with regard to (a) eliminate them by making the standard stronger or (b) transfer them to the PICS/service section of SCL file to make them machine processable. (20180613)WG 10 (completion date Ed 3), standard 7-2, for example PIXIT Gs4 should be defined in standard? To review complete PIXIT with regards: a) eliminate them by making the standard stronger or b) transfer them to the PICS/service section of SCL to make them machine processable c) If a lower value StNum is received and it is not the case of rollover and there is no communication loss then the older/lesser StNum shall be ignored. – to update 7-2. (Thierry D., Herb F.). To check 8-1 in case that there is a need for a change (Herb F.).

- Discuss in Upcoming Meeting set to No
- To discuss in WG10 set to No
- Standard(s) changed from 2-Jul to IEC 61850-7-2