

WG16 Issues - CIM Issues #5834

Instructions add new attribute

06/23/2022 10:34 AM - Herbert Falk

Status: Closed	
Priority: Normal	
Target version:	
Author/Contact Info: Becky	Standard(s):
Base Release: iec61970cim17v34_iec61968cim13v12_iec62325cim04v08	Version:
Solution to be Applied To:	Clause: Instructions
Solution Version: iec61970cim17v34_iec61968cim13v12_iec62325cim04v10	Sub-Clause:
Solution Applied By: BLI	Paragraph:
Completion Date: 02/10/2022	Table:
CIM Keywords:	Originally Closed in Version:
Breaking Change:	Origination Date: 01/18/2022
Breaking Change Description:	Origination ID: 16_0118
CIM Impacted Groups: None	Originally Assigned To:
Requestor:	
Description Propose new attribute "bindingDOTType" and deprecate the bindingDOD attribute.	
Proposed Solution Instructions.bindingDOTType: The binding dispatch operating target type describes the binding dispatch operating target values, primarily differentiating among traditional generation set points (type = generation), load set points (type = load), or level changes (type = loadIncrease or loadReduction). Deprecate the attribute bindingDOD. This attribute was to be used for providing binding dispatch operating deltas. With the new bindingDOTType - the deltas are no longer necessary. All DOT values can be provided using the existing attribute bindingDOT.	
Decision 2/10/2022: Team agreed to add new attribute. The bindingDOD will be deprecated.	

History

#1 - 08/08/2022 05:54 PM - Becky Iverson

- Status changed from New to Closed

- Proposed Solution updated