

WG14 Issues - CIM Issues #6636

Update Name model for all XSD based profiles

12/13/2023 07:27 AM - Svein Olsen

Status: New	
Priority: Normal	
Target version:	
Author/Contact Info: Svein Olsen	Standard(s): 61968-3;61968-4;61968-5;61968-6
Base Release:	Version:
Solution to be Applied To:	Clause:
Solution Version:	Sub-Clause:
Solution Applied By:	Paragraph:
Completion Date:	Table:
CIM Keywords: 61970-Core	Originally Closed in Version:
Breaking Change:	Origination Date:
Breaking Change Description:	Origination ID:
CIM Impacted Groups: WG14	Originally Assigned To:
Requestor:	
Description Some of the TF14 XSD based profile only include IdentifiedObject.mRID and Names.name. It is my understanding that most of the profile used the naming model so that a use can read from the message the human readable names. The intention is not to update this information in another system. However, if the name information is needed the IEC 61968-series of XSD based profile should include IdentifiedObject.name and IdentifiedObject.description in addition to Names to be aligned with 61970-301 and 61970-series of profiles and 61968-13. When Names are used it make sense to also include NameType.	
Proposed Solution IEC 61968-series of XSD based profile should include IdentifiedObject.name and IdentifiedObject.description in addition to Names to be aligned with 61970-301 and 61970-series of profiles and 61968-13. When Names are used it make sense to also include NameType.	